



JRU...U



JRU...UU



JRU...UT

JRU-series-crossed-roller-bearing

( Unit ) : mm

Model	Dimensions						Basic rated load		Weight	Corresponding model	
	Inner ring	Outer ring	Width	Pitch diameter	Shoulder height		Radial			THK	IKO
	d	D	B	Dpw	ds	Dh	C	Co			
JRU 1008	10	52	8	27.5	24	31	2.91	2.43	0.12		CRBF108AT
JRU 2012	20	70	12	41.5	37	47	7.35	8.35	0.29	RU42	CRBF2012AT
JRU 2512	25	80	12	52.5	46.5	58.5	8.61	10.6	0.4		CRBF2512AT
JRU 3515	35	95	15	66	59	74	17.5	22.3	0.66	RU66	CRBF3515AT
JRU 5515	55	120	15	85	79	93	20.3	29.5	1	RU85	CRBF5515AT
JRU 8022	80	165	22	124	114	134	33.1	50.9	2.6	RU124	CRBF8022A
JRU 8022G	80	165	22	124	114	134	33.1	50.9	2.6	RU124G	CRBF8022AD
JRU 8022X	80	165	22	124	114	134	33.1	50.9	2.6	RU124X	CRBF8022AT
JRU 9025	90	210	25	147.5	133	162	49.1	76.8	4.9	RU148	
JRU 9025G	90	210	25	147.5	133	162	49.1	76.8	4.9	RU148G	
JRU 9025X	90	210	25	147.5	133	162	49.1	76.8	4.9	RU148X	
JRU 11528	115	240	28	178	161	195	80.3	135	6.8	RU178	
JRU 11528G	115	240	28	178	161	195	80.3	135	6.8	RU178G	
JRU 11528X	115	240	28	178	161	195	80.3	135	6.8	RU178X	
JRU 16035	160	295	35	227.5	208	246	104	173	11.4	RU228	
JRU 16035G	160	295	35	227.5	208	246	104	173	11.4	RU228G	
JRU 16035X	160	295	35	227.5	208	246	104	173	11.4	RU228X	
JRU 21040	210	380	40	297.3	272	320	156	281	21.3	RU297	
JRU 21040G	210	380	40	297.3	272	320	156	281	21.3	RU297G	
JRU 21040X	210	380	40	297.3	272	320	156	281	21.3	RU297X	
JRU 35045	350	540	45	445.4	417	473	222	473	35.4	RU445	
JRU 35045G	350	540	45	445.4	417	473	222	473	35.4	RU445G	
JRU 35045X	350	540	45	445.4	417	473	222	473	35.4	RU445X	